

Heavy Duty Gas Water Heaters

Model 613050



Heavy Duty - 613050				
WARRANTY	DELIVERY	MAINS PRESSURE	LOCATION	SPECIAL FEATURES
5 YEAR WARRANTY	50L	MAINS PRESSURE	INDOOR & OUTDOOR	<ul style="list-style-type: none"> DESIGNED FOR LONGER LIFE PROVIDES 82°C FOR SANITISING EQUA-FLOW® MANIFOLD FLEXIBILITY

- Ideal for wherever large quantities of hot water are required
- The cylinder is lined with two coats of specially developed vitreous enamel
- Larger mass anode
- Quick recovery
- Equa-Flow® System allows for flexibility in installations

ADD TO PROJECT PROPOSAL

PERFORMANCE

Units in Parallel	Input (kW)	Required Temperature Rise
1	Select Input	Enter Value <input type="text"/> °C (20 ~ 70°C) GO
Delivery (L)	Recovery (L/hr)	1st Hour Delivery (L)
<input type="text"/>	<input type="text"/>	<input type="text"/>

TECHNICAL INFORMATION

Max Thermostat Setting (°C):	82
Min Thermostat Setting (°C):	60
Water Connection ("/mm):	RP 1¼/32
T&PR Connection ("/mm):	RP ¾/20
T&PR Setting (kPa):	1000
Max Water Supply Pressure with ECV (kPa):	680
Max Water Supply Pressure w/out ECV (kPa):	800
Heating Units (elements x kW):	3x3.6,3x4.8
Approx Wt Empty (kg):	34

FAST EMERGENCY, SAME DAY SERVICE
SYDNEY AREA, 7 DAYS